




(JIS マーク認証対象外)

ねじ込み式高圧継手 (ねじ規格 JIS B0203): 45°エルボ

High Pressure Fittings with threads: 45°ELBOW



S80

単位: mm

径の呼び		中心から差込み部底面までの距離 C	ねじの長さ L2	外径 H
A	B			
DN	Nom. Pipe Size			
6	1/8	17	8.8	22
8	1/4	17	11.4	22
10	3/8	19	12.4	26
15	1/2	22	14.9	33
20	3/4	25	16.8	38
25	1	28	19.6	46
32	1-1/4	33	21.9	56
40	1-1/2	35	22.7	62
50	2	43	23.9	75.5
65	2-1/2	52	30.5	93
80	3	64	32.8	110

S160

単位: mm

径の呼び		中心から差込み部底面までの距離 C	ねじの長さ L2	外径 H
A	B			
DN	Nom. Pipe Size			
15	1/2	25	14.9	38
20	3/4	28	16.8	46
25	1	33	19.6	56
32	1-1/4	35	21.9	62
40	1-1/2	43	22.7	75.5
50	2	52	23.9	93
65	2-1/2	64	30.5	110
80	3	64	32.8	121

備考: 製品は JIS B2316 に準拠。ねじは JIS B0203 或は JIS B0202 に準拠。

REMARK: Products refer to JIS B2316; Threads refer to JIS B0203 or JIS B0202