




(JIS マーク認証対象外)

ねじ込み式高圧継手 (ねじ規格 JIS B0203): 異径カップリング

High Pressure Fittings with threads: REDUCING COUPLING



S80

単位: mm

径の呼び		長さ W	外径 D	ねじの 長さ L2	ねじの 長さ L3
A	B				
DN	Nom. Pipe Size				
10 x8	3/8 x1/4	33	25	12.4	11.4
15 x8	1/2 x1/4	37	32	14.9	11.4
15 x10	1/2 x3/8	37	32	14.9	12.4
20 x10	3/4 x3/8	42	38	16.8	12.4
20 x15	3/4 x1/2	42	38	16.8	14.9
25 x15	1 x1/2	45	46	19.6	14.9
25 x20	1 x3/4	45	46	19.6	16.8
32 x15	1-1/4 x1/2	52	55	21.9	14.9
32 x20	1-1/4 x3/4	52	55	21.9	16.8
32 x25	1-1/4 x1	52	55	21.9	19.6
40 x15	1-1/2 x1/2	56	65	22.7	14.9
40 x20	1-1/2 x3/4	56	65	22.7	16.8
40 x25	1-1/2 x 1	56	65	22.7	19.6
40 x32	1-1/2 x1-1/4	56	65	22.7	21.9
50 x15	2 x1/2	66	75	23.9	14.9
50 x20	2 x3/4	66	75	23.9	16.8
50 x25	2 x 1	66	75	23.9	19.6
50 x32	2 x1-1/4	66	75	23.9	21.9
50 x40	2 x1-1/2	66	75	23.9	22.7
65 x25	2-1/2 x 1	71	95	30.5	19.6
65 x32	2-1/2 x1-1/4	71	95	30.5	21.9
65 x40	2-1/2 x1-1/2	71	95	30.5	22.7
65 x50	2-1/2 x 2	71	95	30.5	23.9
80 x32	3 x1-1/4	81	110	32.8	21.9
80 x40	3 x1-1/2	81	110	32.8	22.7
80 x50	3 x 2	81	110	32.8	23.9
80 x65	3 x2-1/2	81	110	32.8	30.5

備考: 製品は JIS B2316 に準拠。ねじは JIS B0203 或は JIS B0202 に準拠。

REMARK: Products refer to JIS B2316; Threads refer to JIS B0203 or JIS B0202.